

## MD-3U26-RMP



MILITARY | SURVEILLANCE | MACHINE VISION | FACTORY AUTOMATION

# MD-3U26-RMP

## Specifications



### CHASSIS

#### Material

SGCC 1.2mm thick aluminum chassis and cover with standard finish

#### Weight

65 lbs. with dual processor motherboard + ATX power supply + (2) hard disks + floppy drive + CD-ROM drive

#### Front Panel Controls

Power ON/OFF  
System Reset switch  
Alarm mute switch  
2 USB ports

#### System Indicators

Power On/Off LED  
Disk Activity LED  
Fan Failure/Overheating Warning LED

#### Dimensions

Height: 5.25" (132 mm)  
Width: 17.00" (430 mm)  
Depth: 26.00" (660mm)

### COOLING FANS

2 x 60mm rear mounted cooling fan kit  
4 x 80mm middle mounted cooling fan kit

### POWER

#### Power Supply

650W Redundant rated switching power supply

### ACCESSIBILITY

Two slide and lock top cover design allows quick access to internal components.

(6) horizontal 5.25" drive bays  
(3) horizontal 3.5" drive bays

### ENVIRONMENT

#### Operating Temperature

0° to 50° C

#### Non-Operating Temperature

-20° to 65° C

#### Humidity

5% to 95% @ 40° C (non-condensing)

#### Altitude

10,000 feet (3048 m)

#### Vibration

Non-operating: 5G, 2-200Hz  
Operating: 5G, 2-200Hz

#### Shock

Non-operating: 35G @ 15-20ms  
Operating: 2.5G 15-20ms

### WARRANTY

ONE YEAR PARTS AND LABOR

*Please contact us for ordering and pricing information.*

**MicroDISC**  
IMAGE PROCESSING SPECIALISTS

301 Oxford Valley Road, Suite 1502  
Yardley, PA 19067

Tel 215.321.9100  
Fax 215.321.9190

[www.microdisc.com](http://www.microdisc.com)  
[sales@microdisc.com](mailto:sales@microdisc.com)